

Shown with optional DCB-05™ and battery back up (left)



ELITE® SWING GATE OPENER

DESIGN YOU CAN'T FAULT

THE OPENER FOR SWING GATES

A proven design that has endured for over 15 years, the performance and strength of the Elite® has made it an industry icon. This unassuming looking opener features a powerful DC motor, robust gearing, articulated arms for smooth operation, and is configurable with 2-, 3- or 5-wire installs.

The Elite® is tough, weather-resistant and built for Australian conditions. At its heart is a powerful DC motor linked to a robust, low maintenance gearbox. This power is transferred to the articulated drive arms, which offer smooth operation and reduced stress on the entire installation. Rounding out this reliable mix are highly effective micro-switch limits that reduce complexity and enhance longevity. When paired with our DCB-05™ Control System it provides a host of operating modes and variations in performance to suit your needs.

WHAT'S IN THE BOX:



Weather resistant opener

AT A GLANCE:



POWERFUL MOTOR

A powerful DC motor linked to a robust gearbox means this opener is both consistent and reliable, and we back this up with a two year guarantee.

SMOOTH OPERATION

The articulated arms provide a smooth opening action for your gates. The system works in the same way your arm would pull the gate open or closed, using a consistent action that reduces stress on the gate, motor and mounting points.

SUITABLE FOR TIGHT SPOTS

The optional minimum sideroom kit allows the Elite® to be fitted even when there is little space between your fully open gates and an adjacent fence or wall

READY FOR DCB-05 INTEGRATION

The strength and robustness of the Elite® is perfect for pairing with our DCB-05™ Gate Control System, which brings smart features, intelligence and security to your gate system.



SMART
SIMPLE
SECURE

ELITE[®] SWING GATE OPENER

TECHNICAL SPECIFICATIONS



Power	Input Voltage	24Vdc
	Motor Type	24Vdc Permanent Magnet
	Motor Power	100W
	Peak Driving Force	200N
	Typical Travel Speed	8° per second
Gate Sizes	Rated Maximum Gate Width	4000mm
	Rated Gate Weight	300kg
Additional Features	Weather Resistance Rating	IP44
Warranty		2 year/5,000 cycles

SAFETY & SECURITY FEATURES



Soft Start/Soft Stop

POWER & MOUNTING SYSTEMS



DC Motor



1x

Single Gate Option



2x

Dual Gate Option



OPERATING MODES & FEATURES



Weather Resistant



Lockout System

ENHANCE YOUR OPENER TO MATCH YOUR LIFESTYLE

When paired with the DCB-05™ Control System you can upgrade with the following accessories:

See our website for our icon glossary explanations.



Battery Back Up In the event of power failure your gate will still work



SmartSolar™ Ready Using only one solar panel the sun does all the work for you



Wireless Keypad Weatherproof, secure access without a transmitter or keys is great for school kids and active families.

Proudly Distributed by:

www.automatictechnology.com.au



www.facebook.com/ATA.Openers

SMART
SIMPLE
SECURE

©2013 Automatic Technology (Australia) Pty Ltd. All rights reserved. The Automatic Technology logos, "smart simple secure" wordage, feature icons, Elite®, DCB-05™ & TrioCode™ are trademarks and registered trademarks of Automatic Technology (Australia) Pty Ltd. No part of this brochure may be reproduced without prior permission. In an ongoing commitment to product quality we reserve the right to change specification without notice. E&OE. 6-8 Freeways Boulevard, Keysborough, Victoria, 3173. Ph: +61 (0) 3 9791 0200. Fx: +61 (0) 3 9791 0250. Printed Oct 2013. 204609 ATA Elite® SGO-1v4.

For more information on this door opener and other Automatic Technology products please visit us online.

automatic
TECHNOLOGY